












MODEL	SERIAL	ANALOG OUT	ETHERNET TCP/IP IP/EIP	MODBUSTCP	OPERATION MODES	STANDARD I/O	TIME & DATE FUNCTION	BATTERY OPTION	EXCITATION	MAX. NO. OF LOAD CELLS	SIGNAL INPUT RANGE	ENCLOSURE / IP RATING	DISPLAY	RESOLUTION NTEP	SENSITIVITY NTEP	RESOLUTION CANADA	SENSITIVITY CANADA	RESOLUTION OIML	SENSITIVITY OIML	NTEP / CANADA	OIML APPROVAL	ETL
 185 185B	1	N/A	N/A	N/A	Remote Indicator, Piece Counting, Millivolt Display, Diagnostic Function	1 bi RS232	No	No / Yes	5.0 vdc	4 (350 Ω)	0 mV to 40 mV	ABS / IP66	1 in high LCD	6,000 (Class III/IIIL)	1.2uV/e	6,000 (Class III/IIHHD)	N/A	6,000 (Class III/IIIL)	1.2uV/e	18-075 / AM-6109	R-76/2006-A-DK2-18.04	No
 190*	1	N/A	N/A	N/A	Checkweighing, Count, Hold, PWC	1 bi RS232	Yes	Yes	5.18 vdc	6 (350 Ω)	0.5 mV to 40 mV	Polycarbonate IP69K	1 in high LCD	100 to 10,000 Class III/IIIL	0.5 μV/d Class III/IIIL	100 to 10,000 Class III/IIHHD	0.5 μV/d Class III/IIHHD	100 to 10,000 Class III 100 to 1,000 Class IIIIL	0.5 μV/d Class III Class IIIIL	10-084 AM-5804	R76/1992-DK3-11.05	No
 200	2	Optional	Optional	Optional	Remote Indicator	1 bi RS232 1 out RS232/20mA 2 out 20mA 4 remote in	No	No	8/12 vdc	8 (350 Ω)	1.0 mV to 40 mV	Aluminum IP52	0.6 in high LED	100 to 10,000 Class III/IIIL	0.3 μV/d Class III/IIIL	100 to 10,000 Class III/IIHHD	0.3 μV/d Class III/IIHHD	100 to 10,000 Class III 100 to 1,000 Class IIIIL	0.7 μV/e Class III Class IIIIL	01-011 AM-5337R3	R76/1992-DK1-01.02	Yes
 201	1	Standard	Standard	Standard	Digital Fill Control, ColorZone, Checkweighing, Web Interface through IP Address	1 bi RS232 or 1 bi RS485 4 iso inp, 4 iso out 1 10/100 TCP/IP/EIP 1 (mini USB-B)	Yes	No	11.72 vdc	8 (350 W)	0.5 mV to 35 mV	Aluminum 35-mm DIN Rail / IP20	0.5 in high LCD	10,000 (Class III/IIIL)	0.5 uV/d	10,000 (Class III/IIHHD)	N/A	N/A	N/A	13-028 / AM-5904C	N/A	No
 205	2	Optional	Optional	Optional	Remote Indicator, SnapStream	1 bi RS232 1 out RS232 2 out 20mA 4 remote in	No	No	12 vdc	8 (350 Ω)	1.0 mV to 40 mV	Stainless Steel IP67	0.6 in high LED	100 to 10,000 Class III/IIIL	0.3 μV/d Class III/IIIL	100 to 10,000 Class III/IIHHD	0.3 μV/d Class III/IIHHD	100 to 10,000 Class III 100 to 1,000 Class IIIIL	0.7 μV/e Class III Class IIIIL	01-011 AM-5397R3	R76/1992-DK1-01.02	Yes
 210	2	Optional	Optional	Optional	Axle Weigher, Checkweighing, PWC, Count, Remote Indicator, SnapStream	1 bi RS232 1 out RS232 2 out 20mA 4 remote in 3 cont. out	Yes	No	8/12 vdc	8 (350 Ω)	1.0 mV to 40 mV	Stainless Steel IP67	0.6 in high LED	100 to 10,000 Class III/IIIL	0.3 μV/d Class III/IIIL	100 to 10,000 Class III/IIHHD	0.3 μV/d Class III/IIHHD	100 to 10,000 Class III 100 to 1,000 Class IIIIL	0.7 μV/e Class III Class IIIIL	01-011 AM-5397R3	R76/1992-DK1-01.02	Yes
 210-FE	2	Optional	Optional	Optional	Axle Weigher, Checkweighing, PWC, Count, Remote Indicator, SnapStream	1 bi RS232 1 out RS232 2 out 20mA 4 remote in 3 cont. out	Yes	No	8/12 vdc	8 (350 Ω)	1.0 mV to 40 mV	Stainless Steel IP66	2.5 in high LED	100 to 10,000 Class III/IIIL	0.3 μV/d Class III/IIIL	100 to 10,000 Class III/IIHHD	0.3 μV/d Class III/IIHHD	100 to 10,000 Class III 100 to 1,000 Class IIIIL	0.7 μV/e Class III Class IIIIL	01-011 AM-5397R3	R76/1992-DK1-01.02	No
 212X*	2	Optional	Optional	Optional	ID Storage, Fill Control, Remote Indicator	1 bi RS232 1 out 20mA 4 remote in 3 cont. out	Yes	No	12 vdc	8 (350 Ω)	1.0 mV to 40 mV	Polycarbonate IP66	2 in high LCD	N/A	N/A	N/A	N/A	N/A	N/A	N/A N/A	N/A	No
 212GX*	2	Optional	Optional	Optional	Axle Weigher, Checkweighing, PWC, Count, Remote Indicator, SnapStream	1 bi RS232 2 out 20mA 1 out RS232 4 remote in 3 cont. out	Yes	No	8/12 vdc	8 (350 Ω)	1.0 mV to 40 mV	Polycarbonate IP66	2 in high LCD	100 to 10,000 Class III/IIIL	0.3 μV/d Class III/IIIL	100 to 10,000 Class III/IIHHD	0.3 μV/d Class III/IIHHD	100 to 10,000 Class III 100 to 1,000 Class IIIIL	0.7 μV/d Class III Class IIIIL	01-011 AM-5397R3	N/A	No
 225	4	Optional	Optional	Optional	ID Storage, Fill Control, Batching, Checkweighing, ICAN, SCD, RI, SnapStream, 3 Scale	3 bi RS232 1 bi 20mA 1 out RS232/20mA 8 remote in 16 control out	Yes	No	12 vdc	14 (350 Ω) 8 (350 Ω) for OIML applications	1.0 mV to 40 mV	Stainless Steel IP66	5 x1.33 in 240 x 64 dot matrix LCD	100 to 10,000 Class III/IIIL	0.3 μV/d Class III/IIIL	100 to 10,000 Class III/IIHHD	0.3 μV/d Class III/IIHHD	100 to 10,000 Class III 100 to 1,000 Class IIIIL Dual Interval	0.7 μV/e Class III	01-011 AM-5670C	R76/1992-DK1-08.02	Yes
 825	4	Optional	Standard	Optional	ID Storage, Fill Control, Batching, Checkweighing, Fully-Programmable	2 bi RS232 1 bi RS232/20mA 1 bi RS232/RS485 4 iso inp, 4 iso out 1 10/100 TCP/IP/EIP 2 USB A, 1 USB B	Yes	No	10.85 vdc	14 (350 Ω)	1.0 mV to 40 mV	Stainless Steel IP66	5.25 x 4 in 640 x 480 dot matrix LCD	100 to 10,000 Class III/IIIL	0.3 μV/d Class III/IIIL	100 to 10,000 Class III/IIHHD	0.3 μV/d Class III/IIIL	100 to 10,000 Class III 100 to 1,000 Class IIIIL Dual Interval	0.5 μV/e Class III Class IIIIL	08-046 AM-5700C	R76/1992-DK1-08.03	Yes

*DC and battery option available on certain models